EKASTU | Safety WIR PRODUZIEREN SICHERHEIT!

Technical Data Sheet

Chemical Protection Gloves 628



Order no.: 381 628 EAN: 4013207381601

Product designation:

EKASTU-Chemical Protection Gloves 628 (Size 10)

Protection against mechanical risks and certain chemicals such as fats, oils, most acids and bases.



DESCRIPTION

Chemical Protection Gloves can be used anywhere, where greasy materials are handled or where acids, alkalis and corrosive solids are handled, posing a risk to the surface of the hand

- Category 3, type A
- Length: approx. 28cm; colour: green; Size: 10
- Very durable version
- Fully coated with polyvinyl chloride
- Cotton lined and extremely abrasion-resistant
- Durable through double-dipping process
- · Better palpation ability and around up to 50% less tiredness for the hand
- · Optimal abrasion resistance according to EN 388, therefore long service life

MAIN FEATURES

Mechanical Characteristics	
Abrasion resistance (A)	3
Cut resistance according to Coup-Test (B)	1
Tear resistance (C)	2
Puncture resistance (D)	1
Cut resistance according to ISO (E)	Х
Protection against impact (F)	Х

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- CE-Identification
- Notified body
- Applied standard
- Consider the information brochure
- Size

STORAGE

- · Ambient temperature. Protect against cold, heat and humidity
- · Consider conditions noted on the packaging

CERTIFICATIONS

- Chemical Protection Gloves are certified according to EN ISO 374-1:2016+A1:2018/Typ A, EN ISO 374-5:2016, EN 388:2016+A1:2018, EN ISO 21420:2020
- Certified according to European Regulation (EU) 2016/425

WARNING REFERENCE

• Use in accordance with the requirements only!

USER REFERENCES

Marking of chemical protective gloves Marking according to EN ISO 374:2016 EN ISO 374-1/ Type A Performance level 2 M3-PLUS (Penetration time > TYPE A 30 minutes) M2-PLUS for at least 6 of 18 6 Series test chemicals abcdef EN ISO 374-1/ Type B Performance level 2 (Penetration time > **TYPE A includes** TYPE B 30 minutes) TYPE B for at least 3 of 18 test chemicals abo EN ISO 374-1/ Type C Performance level 1 (Penetration time > TYPE A and TYPE C 10 minutes) **TYPE B includes** for at least 1 of 18 TYPE C test chemicals

MATERIALS

- Outside of gloves: Polyvinyl chloride (PVC) 0,80mm
- Inside of gloves: Cotton (knitted) 0,40mm

WEIGHT

• approx. 180 g

DONNING AND USING

• Take the Protection gloves from the packing directly before use. Use the Protection gloves in accordance with the information brochure.

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Protection gloves with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-195 "Use of Protection Gloves".

TD 381 628 English_01-01.25

EKASTU Safety GmbH Schänzle 8 • D-71332 Waiblingen Germany Tel.: +49(0)7151 975099-0 Fax: +49(0)7151 975099-30 Internet:www.ekastu.de eMail: info@ekastu.de