



Order no.: 466 701

Product designation:

Full Face Mask C 701 (Class 3) olive/black

In connection with respiratory filter (standard thread EN 148-1) as filtering device - directly or by means of breathing assistance AIRMATIC.
The scope of protection is determined by the product information, technical standards and valid application rules.



DESCRIPTION

Innovative inspiration system with rectangular inhalation valve and absence of non-return valves, which ensures excellent anti-fog, assuring a minimum level of breathing resistance

Panoramic visor, optical class 1 (EN 166), ensures a wide field of vision, without optical distortions

- Ballistic resistance (STANAG 2920)

Inner half mask and faceblank in thermoplastic

- Excellent adaptability to different facial conformation
- Hypoallergenic material

Comfortable harness fixed on 5 points made of EPDM

Approved for firefighters

MAIN FEATURES



PERFORMANCES



Sturdiness



Comfort



Panoramic view



Ergonomics



Easy maintenance

APPLICATION FIELDS



Marine



Industry



Hospital



Chemical Pharmaceutical Industry



Agriculture

MATERIALS

- Face seal: Thermoplastic rubber (TPR)
- Inner half mask: Thermoplastic rubber (TPR)
- Disk-Frame: Polyamide (PA)
- Visor: Polycarbonate (PC)
- Inhalation valve: Silicone
- Connector: Polyamide (PA)
- Connector-Clip: Polyamide (PA)
- Harness: Ethylene-Propylene-Diene-Mixture (EPDM)

WEIGHT

- approx. 620 g

MARKING

- Trade mark of manufacturer (LOGO)
- Product designation
- Applied standard
- Manufacture year and -month
- CE-Identification
- Notified body
- Type identifying marking

DONNING AND USING

- Take the Full face mask from the Packing and/or Storage container directly before use
- Use the Full face mask in accordance with the information brochure

STORAGE

- Ambient temperature. Protect against cold, heat and humidity
- Consider conditions noted on the packaging
- Not higher than 50°C

CERTIFICATIONS

- The mask is certified as class 3 according to EN 136 (maximum mechanical, heat and flame resistance)
- For use with particle, gas and combined filters equipped with EN 148/1 threaded connection
- Certified according to European Regulation (EU) 2016/425

USER REFERENCES

EKASTU Safety GmbH guarantees the indicated achievement according to class and type. It is to be noted that the laboratory test values can considerably deviate from those, which are reached in practice. The user must read and understand all functional information. Use the Respiratory protective devices with this information brochure, the relevant valid statutory regulations and the safety requirements of the profession associations, particularly the regulations for use in accordance with DGUV Rule 112-190 resp. DIN EN 529 „Respiratory protective devices – recommendation for selection, use, care and maintenance – guidelines“.

TD 466701 English_03-01.24